

General Equipment list - North America

GENERAL SPECIFICATIONS

Overall Length (L.O.A)	14,60 m	47'11"
Hull length	13,65 m	44'9''
• L.W.L.	13,24 m	<i>43'5"</i>
Hull Beam	4,50 m	14'9"
Deep draft (Cast iron)	2,35 m	7'9"
 Deep ballast weight 	2 735 kg	6,028 lbs
 Shallow draft (Cast iron) 	1,75 m	5'9"
 Shallow ballast weight 	3 061 kg	6,746 lbs
 Performance draft (Cast iron/Lead) 	2,65 m	8'8"
 Ballast weight performance 	2 576 kg	5,678 lbs
Air draft	20,31 m	66'8"
 Air draft (Mast Performance) 	21,31 m	69'11"
Light displacement	10 597 kg	
 Fuel tank capacity (standard) 	200 L	53 US Gal
 Fuel tank capacity (Option) 	200 L	53 US Gal
 Fresh water capacity (standard) 	370 L	98 US Gal
 Fresh water capacity (Option) 	200 L	53 US Gal
 Engine power (standard) 	57 HP	57 HP
 Engine power (Option) 	80 HP	80 HP

ARCHITECTS / DESIGNERS __

- · Naval Architect: Pascal Conq
- Outside & interior design: Nauta Design

EC CERTIFICATION *_

- Category A 10 people
 Category B 11 people
 Category C 12 people

STANDARD SAILS DIMENSIONS _____

 Furling mainsail (standard) Self-tacking jib (standard) Classic mainsail Furling genoa (109 %) 	44,50 m² 40,42 m² 54 m² 52,16 m²	561sq/ft
Code 0Asymmetrical spinnakerI	102 m ² 152 m ²	,
J P - Roller furling mast	17,72 m 5,72 m 16.57 m	18'9" 54'4"
P - Classic mast E	16,82 m 5,630 m	55'2" 18'6"

PERFORMANCE (Extended classic mast)

FLIN ONWANCE (Extended classic mast)		
Classic mainsail	57,60 m ²	620 sq/ft
Genoa	57,80 m ²	622 sq/ft
• 1	18,33 m	60'2"
• J	5,71 m	18'9"
• P	17,82 m	58'6"
• E	5,63 m	18'6"



3 cabins 2 heads version:



3 cabins 3 heads version:




4 cabins 2 heads version:



4 cabins 4 heads version:



5 cabins 3 heads version:





General Equipment list - North America

STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to CE certification
- Monolithic polyester contact hull
- Monolithic contact structural counter mold (Fabric resin) bonded to the hull
- Injected deck construction in fiberglass and Saerform foam sandwich, covered with non-slip diamond pattern
- · Cast iron keel fixed with bolts and stainless steel backing plates
- Twin rudders affixed with stainless steel stock
- White hull Grey metal hull decoration
- 8 Hull portlights

DECK EQUIPMENT_

RIGGING

- Anodized aluminum mast, deck stepped with in-mast furling system, 2 Aft swept spreaders
- Anodized aluminum boom
- · Cathedral type single-strand stainless steel standing rigging
- Split backstay
- · Rigid boom vang
- · Self-tacking jib with on-deck furler
- · 2 Stand Up mainsheet blocks on the coachroof
- 1 Self-tacking jib track with traveller
- All lines lead back to the helm stations (except boom topping lift and genoa halyard)
- Complete running rigging: Main halyard, Genoa halyard with cleat on mast, Boom topping lift with cleat on mast, Mainsheet, 1 Selftacking jib sheet
- 6 Clutches
- · Halyard covers
- · 2 Flag halyards

WINCHES

- 1 Self tailing winch (H40.2 STA) at each helm station
- · 1 Aluminum Speed Grip winch handle
- · 2 Winch handle holders

SAILS

- Furling mainsail Dacron, with UV protection Natural, horizontal cut (North Sails)
- Self-tacking jib Dacron with UV protection Natural, horizontal cut (North Sails)

MOORING - ANCHORING GEAR

- Self-draining chain locker Clench bolt Hatch cover
- · Single roller stainless steel bow fitting with offset roller
- 12 V 1 000 W vertical electric windlass Remote control
- 6 Aluminum mooring cleats, Length: 400 mm / $15^3/_4$ " Stainless steel chafing plate

SAIL LOCKER

- Access by polyester cover, Passage width: 65 x 50 cm / 2'2" x 1'8"
- · Stainless steel ladder
- · Shelving unit

SAFETY ON DECK

- · 1 Open stainless steel pulpit
- · 2 Stainless steel aft pushpits
- · 2 stainless steel handrails on coachroof
- · 1 Ring lifebuoy bracket
- · Welded ring on pushpit for flag
- Double life lines and stainless steel stanchions, 650 mm / 2'2"
- · Emergency ladder on pushpit

COCKPIT

- Self-bailing cockpit
- 1 Watertight compartment under cockpit benches & 1 Wet locker
- · 1 Locker in cockpit bottom
- 1 Gas compartment under port helmsman seat
- · Natural solid wood slatted cockpit benches
- · Solid wood slatted helm seats with starboard storage locker
- Foldaway helmsman foot chock
- 2 Steering wheel consoles: Stainless steel steering wheels (900 mm diameter / 2'11") Anthracite leather covering Steering gear at the helm station Steering line transmission system Stainless steel handrail
- · 2 Deck accesses for emergency tiller
- 1 Emergency tiller
- · 1 Steering compass on the cockpit table
- · Engine throttle and control panel on starboard
- Cockpit table, stainless steel support, 2 wooden flaps, lighting, 4 cupholders, stainless steel handrail, BIB storage
- 1 Cockpit shower with mixer tap
- 1 PMMA companionway door in 2 removable parts Sliding hatch made of PMMA

SWIM PLATFORM / STERN DECK

- Fully opening transom, convertible into swim platform (2,65 m x 0,80 m / 8'8" x 2'7")
- · Intermediate cockpit access step
- · Manually controled
- Natural solid wood decking on swim platform
- 1 Stainless steel, removable bathing ladder with dedicated stowage in the cockpit




General Equipment list - North America

INTERIOR

- · Woodwork Alpi Walnut
- · Rovere Aleve Parquet type laminated floorboards
- · Interior cushions in cloth
- · Padded lining in salon (Beige)
- · Mattresses in the cabins, HR35kg/m3 foam

Standard version: 3 cabins 2 heads version



COMPANIONWAY

Headroom: 1,98 m / 6'6"

- Wooden salon companionway with molded wood hanging steps with non-slip surface
- 1 Stainless steel handrail with anthracite leather sheathing (to port)

SALON - STARBOARD

Headroom: 2,01 m / 6'7"

- · U-shaped salon bench
- Salon table wooden top
- · Central seat facing the table, without backrest
- · Mirror on bulkhead, at base of companionway
- Storage under bench seats
- · Bookshelf against forward bulkhead
- 1 Electrical panel for access to electrical connections (to starboard)
- · 2 Hull portlights
- 2 Coaming glazing
- · 2 Opening deck hatches with mosquito screens/blinds

CHART TABLE & SOFA - PORTSIDE

Headroom: 1,94 m / 6'4"

- · Table with storage molded wood fiddle Laminated covering
- · Meridian function seat facing the salon
- · 2 USB sockets
- 1 Hull portlight

GALLEY - PORTSIDE

Headroom: 1,94 m / 6'4"

- L-shaped kitchen
- · Counter-top in Clay compact with Corian fiddles
- Stainless steel sink 2 rectangular basins 1 Faucet with hot/cold water under pressure - Clay compact sink cover with cutting board function on back
- 1 Gas stove 2 burners Stainless steel oven on gimbal Stainless steel protection handrail
- 1 85 L ice box, top opening (without refrigeration unit)
- 1 130 L refrigerator (12 V), front opening
- Fitted cupboards and closed cubbyholes
- Bin under sink
- · Low unit: 1 Drawer, 2 Doors against companionway bulkhead
- 1 Opening portlight with curtains in the coachroof side window
- 1 Hull portlight

OWNER'S CABIN

Headroom: 1,95 m / 6'5"

- Central double bed (2,00 m x 1,53 m x 1,23 m / 6'7" x 5' x 4')
- 2 Hanging lockers, Open storage compartment along the hull,
- 6 Upper lockers, 1 Drawer under the bed
- 1 Storage locker either side of the bed
- 2 Night tables
- 2 Flexible and adjustable bedside lamps
- · 2 USB sockets
- · 2 Flush deck hatches with mosquito screen/blind
- · 2 Hull portholes with sliding blind

2 PRIVATE HEADS:

Headroom: 1,93 m / 6'4"

to port:

- Manual marine toilet
- 1 50 L / 13 US Gal Rigid holding tank
- · 1 Polyester basin Mixer tap
- 1 Cabinet Mirror
- Toilet accessories
- 1 Deck hatch with mosquito screen/blind

o starboard:

- · Shower with wooden seat, white polyester shower base
- · 2 Storage closets
- · 1 Deck hatch with mosquito screen/blind
- · Sink with mixer tap

PORT AFT CABIN

Headroom: 1.92 m / 6'4"

- 1 Double bed (2,05 m x 1,40 m / 6'9" x 4'7")
- 1 Hanging locker 2 Cupboard units 1 Cubby hole locker
- 1 Bed access sideboard
- · 2 Flexible and multi-directional reading lights at headboard
- 2 USB sockets
- · 1 Hull porthole with sliding blind
- 1 Cockpit opening window with curtain under cockpit seats
- 1 Fixed cockpit window with curtain on the coaming

STARBOARD AFT CABIN

Headroom: 1,92 m / 6'4"

- 1 Double bed (2,05 m x 1,40 m / 6'9" x 4'7")
- 2 Cupboard units 1 Cubby hole locker
- 1 Bed access sideboard
- · 2 Flexible and multi-directional reading lights at headboard
- · 2 USB sockets
- 1 Hull porthole with sliding blind
- 1 Cockpit opening window with curtain under cockpit seats
- 1 Fixed cockpit window with curtain on the coaming

OWNER'S HEAD - STARBOARD

Headroom: 1,92 m / 6'4"

- · Access from the salon or the starboard aft cabin
- Separate shower Self-draining storage bin 1 Mixer tap White polyester shower base
- 1 Manual marine toilet
- 1 64 L / 17 US Gal Rigid holding tank
- 1 Polyester basin 1 mixing tap hot/cold water
- 1 Cabinet + Storage space under the basin
- 2 Mirrors
- · Toilet accessories
- · 2 Opening ports on coaming with curtains on side windows



General Equipment list - North America

3 cabins 3 heads version



Large lengthways galley facing the salon instead of the starboard so-

Central unit against central seat, backrest function. The starboard aft cabin hanging locker is reduced.

OWNER'S HEAD - PORTSIDE

- · Access from the salon or the aft cabin
- · 1 Manual marine toilet
- 1 64 L / 17 US Gal Rigid holding tank
- 1 Polyester basin 1 mixing tap hot/cold water
- · 2 Mirrors
- · Toilet accessories
- · 1 Opening portlight with curtains in the coachroof side window

LENGTHWAYS GALLEY COUNTER

- · Counter-top in Clay compact with Corian fiddles
- Stainless steel sink 2 rectangular basins 1 Faucet with hot/cold water under pressure - Clay compact sink cover with cutting board function on back
- 1 Gas stove 2 burners Stainless steel oven on gimbal Stainless steel protection handrail
- 1 85 L ice box, top opening (without refrigeration unit)
- 1 130 L refrigerator (12 V), front opening
- 3 Closed high shelves, 1 High open cubby hole locker
- · Bin with access on the counter-top
- 1 Lower unit: 3 Storage drawer
- 1 Low unit: 1 Drawer 1 Door
- · 1 Opening portlight with curtains in the coachroof side window
- 1 Hull portlight

4 cabins 2 heads version



The starboard head of the standard version is replaced by a cabin with bunk beds:

- Headroom: 1.92 m / 6'4"
- 2 Bunk beds: Top bunk (2,04 m x 0,67 m 0,53 m / 6'8" x 2'2" 1'9") Bottom bunk (2,00 m x 0,60 m 0,42 m / 6'7" x 2' 1'5")
- Storage
- · 1 Opening porthole with curtain

4 cabins 4 heads version



The salon is unchanged. The cabins and heads are identical to version 3 cabins, 3 heads.

Forward: 2 cabins each with their private head.

5 cabins 3 heads version



The starboard head of the standard version is replaced by a cabin with bunk beds:

- Headroom: 1,92 m / 6'4"
- 2 Bunk beds: Top bunk (2,04 m x 0,67 m 0,53 m / 6'8" x 2'2" 1'9") Bottom bunk (2,00 m x 0,60 m 0,42 m / 6'7" x 2' 1'5")
- Storage
- · 1 Opening porthole with curtain

2 SYMMETRICAL FORWARD CABINS

Headroom: 1,95 m / 6'5"

- 1 Double bed (2 m x 1,40 m x 0,80 m / 6'7" x 4'7" x 2'7")
- 1 Hanging locker 2 Closed high shelves, 2 Open cubbyholes,
- 1 Drawer under the bed
- · 1 Swivelling reading light
- 1 Deck hatch with mosquito screen/blind
- 1 Hull porthole with sliding blind
- 2 USB sockets
- Access door to the head



General Equipment list - North America

ENGINE

- · Engine Yanmar Diesel:
 - 57 HP/57 HP, Common Rail (standard)
 - 80 HP/80 HP, Common Rail (Option)
- Engine control at the starboard helm station Control panel
- Engine compartment: Soundproofing foam Ventilation: 3 air intakes and 1 forced air outlets
- 1 Alternator 12 V / 125 Amp
- 1 Rotomolded diesel tank 200 L / 53 US Gal (under starboard aft berth) Electronic gauge Low level alarm 1 Tank filling access
- Filters: Sea water Diesel Water separator
- · Fixed three blade propeller
- 1 Engine access through companionway (opening with 2 gas pistons) 2 Engine access through aft cabins

ELECTRICITY

- 12 V Circuit
- 2 Service batteries (120 Amp) 1 Engine battery (120 Amp)
- · 1 Load balancer
- 12 V Electrical panel (Fuses Voltmeter Water gauge Fuel gauge Battery warning Fuel warning Water warning)
- 3 230V Sockets
- · 9 USB sockets
- 1 Shore power socket (230 V)
- Lighting: Overhead lights Reading lights Reading light, flexible and multi-directional
- LED navigation lights: 1 Masthead light 1 Steaming light 1 Mooring light on masthead
- Wire runs for optional cables

PLUMBING

- 1 Rotomolded freshwater tank 330 L / 87 US Gal, under berth in forward cabin 1 Tank filling access
- · Waterpressure system Expansion tank Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump

GAS_

- 1 Box for 2 gas bottles in the cockpit (diameter: 0,28 m/ 11" x Height: 0,44 m/ 1'5")
- Regulator and solonoid
- · Gas leak detector



ceanis 46.1)

General Equipment list - North America

TRIM LEVEL & PACKS

COMFORT TRIM LEVEL

- Cockpit bench extensions + 2 halyard bags below
- Hifi: Fusion + Interior speakers & Waterproof exterior speakers
- · Salon & Galley: LED indirect lighting
- Galley: Stainless steel cooker 2 burner oven/broiler on gimbal
- Galley: Refrigeration system, 12 V, in top-opening icebox (for storage below 0°C)
 Galley: Compact sink cover Clay with cutting board
- · Yacht Case Tableware
- Upholstery padding (Cabins): Beige
- Battery charge display, Navicolor screen (3,5")
- 3 Additional 100 ampères service batteries
- 1 Additional 40 ampères battery charger
- · AGM Batteries instead of standard
- · Mosquito screens on portholes
- · Access openings to port and starboard

ELECTRONICS PACKS: B&G

COASTAL PACK

- Starboard steering console: 1 Multifunction touchscreen Zeus³ 7" wide wireless (GPS, Chart plotter, Chart reader Cartography Navionics Silver included)
- · Windex Windvane
- · Wind Sensor (Windvane, Anemometer)
- Sensor (Log, Speedometer, Temperature)
- NAC3 Autopilot + Starboard helm console control
- · Fixed V60 VHF, AIS receiver function
- Protective cover (Cadet Grey):
 - to starboard: Steering wheel & console
 - to port: Steering wheel

OFFSHORE PACK (implies pack Coastal)

- Port steering console: 1 Multifunction touchscreen Zeus³ 7" wide wireless (GPS, Chart plotter, Chart reader Cartography Navionics Silver included)
- 1 Triton² display
- WR10 Wireless autopilot remote control
- · PC interface
- Protective cover (Cadet Grey): Steering wheel & console

COASTAL + OFFSHORE PACK - LARGE CONSOLES (requires the bow thruster)

- · XXL consoles to port and starboard
- 1 Multifunction touchscreen Zeus³ 9", on each console
- · Electric engine controls, on the starboard console
- · Wind Sensor (Windvane, Anemometer)
- · Sensor (Log, Speedometer, Temperature)
- NAC3 Autopilot + Remote control, on the port console
- · WR10 Wireless autopilot remote control
- · Fixed V60 VHF, AIS receiver function
- 1 Triton² display, on the port console
- · PC interface
- Protective cover (Cadet Grey): Steering wheel & console
- · Windlass control with chain counter, on the starboard console
- · Bow thruster control, on the starboard console

FASNET PACK

(requires the First Line pack and makes the Coastal pack obligatory)

- · 3 Mast foot repeaters
- AIS 500
- · H50 Wireless VHF set



General Equipment list - North America

PERFORMANCE PACK

Optional sails (Lite Skin):

Sail surfaces for information: Classic mainsail (58 m² / 624 sq/ft), Genoa (62 m² / 667 sq/ft)

FIRST LINE ALU PACK

- · Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker)
- Performance Classic aluminum mast (Z Diffusion), 2 Aft swept spreaders (+ 1 m / 3'3"). Track + Main sail ball-bearing traveler
- · Textile hydraulic backstay
- · Cathedral type Dyform standing rigging
- · Flatdeck genoa furler
- 4 Additional halyard clutches (2 to starboard + 2 to port)
- Performance running rigging, Dyneema (Mainsail, Genoa, Code 0, Asymmetrical spinnaker, Halyards)
- German system (Two-way mainsheet at the helm station)
- · Harken pulleys upgrade: 12 Black Magic, 8 Element (instead of standard)
- Genoa sheet tracks on side decks + Complete genoa rigging (Genoa sheets, Genoa cars)
- Performa winches upgrade (1 Port electric H46.2 STPEH rigging winch (Halyards) + 1 Starboard manual H46.2 STP rigging winch + 2 Manual H50.2 STP genoa sheet winches)
- · White or black composite steering wheels
- · First Line hull graphics (red)

FIRST LINE CARBON PACK

- · Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker)
- Performance classic carbon mast (Axxon), 2 Black anodized aluminum aft swept spreaders (+ 1 m / 3'3"). Track (Harken) + Main sail ball-bearing traveler
- · Textile hydraulic backstay
- · Black anodized aluminum boom
- · Cathedral type Dyform standing rigging
- · Flatdeck genoa furler
- 4 Additional halyard clutches (2 to starboard + 2 to port)
- Performance running rigging, Dyneema (Mainsail, Genoa, Code 0, Asymmetrical spinnaker, Halyards)
- German system (Two-way mainsheet at the helm station)
- Harken pulleys upgrade: 12 Black Magic, 8 Element (instead of standard)
- Genoa sheet tracks on side decks + Complete genoa rigging (Genoa sheets, Genoa cars)
- Performa winches upgrade (1 Port electric H46.2 STPEH rigging winch (Halyards) + 1 Starboard manual H46.2 STP rigging winch + 2 Manual H50.2 STP genoa sheet winches)
- · Black composite steering wheels
- · First Line hull graphics (red)

RIGGING PACKS

	PACK		PACK DOWNWIND
	DOWNWIND	UPWIND	+ UPWIND
2 Genoa winches (H50.2 STA)	•	•	•
German system (Two-way mainsheet at the helm station)	•		•
Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0	_		_
and asymmetric spinnaker)			•
Asymmetrical spinnaker rigging			
2 Additional halyard clutches			
Genoa sheet tracks on side decks		•	
Furling Dacron genoa (to replace the standard self-tacking jib)		•	

CLASSIC MAST PACK __

- Classic ⁹/₁₀ anodized aluminum mast, 2 Spreaders
- Dacron semi Full Batten mainsail
- 2 Additional halvard clutches (to port)
- · Lazy Jack System and Lazy bag in Natural color

TENDER PACK _

- Retractable davits (Max. tender length: 3,10 m / 10'2", Maximum load: 130 kg / 287 lbs)
- · Electric inflator / deflator
- · Outboard engine bracket



General Equipment list - North America

OPTIONS

NAVIGATION ELECTRONICS: B&G

- 4G Radar
- Chart table: Multifunction Zeus³ 9" wide wireless screen
- · H50 wireless VHF set
- AIS 500
- Forward Scan Sensor (Forward underwater vision)
- 9" screen upgrade (with the Offshore pack)

RIGGING - SAILS

- Code 0 with "Top Down" furling system (incompatible with ICW mast, Incompatible with First Line Pack)
- Hydraulic backstay (for standard low air draft classical mast incompatible with mast with in-mast furling and ICW and First Line pack)
- 1 GRP mainsail arch with 2 Stand-Up mainsheet blocks
- Roller furling mast ICW + Genoa Dacron (I: 16,92 m / 55'6"; P: 15,75 m / 51'8"; Furling mainsail: 41 m² / 440 sq/ft; Genoa: 51 m² / 548 sq/ft)
- Staysail rigging (Halyard sheave with block + Releasable forestay chainplate + 1 Self-tacking staysail sheet)

WINCHES

- 1 Port electric primary winch H46.2 STAEH (instead of standard -Incompatible with First Line Pack)
- 1 Starboard electric primary winch H46.2 STAEH (Incompatible with First Line Pack)
- 2 Electric genoa winches H50.2 STAEH + 1 Winch handle (Incompatible with First Line Pack)
- 1 Harken Performa starboard maneuver electric winch (implies pack First Line)
- 2 Electric Harken Performa genoa sheet winches H50.2 STP (implies pack First Line)

HULL - DECK - COCKPIT

- Pearl grey gel-coat (with matching sticker on the halyard covers)
- · Solid wood decking on cockpit sole
- Solid wood slatted side decks
- Solid wood decking on sunbeds
- "Luxe" polyester/wood cockpit table + Protective cover (Cadet Grey), Stainless steel handrail, Lighting, Central storage (15 L / 4 US Gal)
- Refrigeration unit for "Luxe" cockpit table
- Cover for standard cockpit table, Cadet Grey
- Gas cockpit griddle
- "Luxe" sprayhood, Windows Extra-Clear, Cadet Grey (2 Versions: with and without mainsail arch)
- Bimini "Luxe", with shading canvas and LED lighting, Cadet Grey (2 Versions: with and without mainsail arch)
- Full cockpit enclosure Cadet Grey
- · Sunshade (Roof), Cadet Grey
- · Cockpit seats Dolce 51
- Cockpit cushions Dolce 51 with seatbacks + 2 Companionway sunbeds with tilting backrests and built-in cup holder
- Tunnel bow thruster + 2 Dedicated batteries (50 Amp 12 V)
- Retractable bow thruster Quick + 2 Dedicated batteries (50 Amp -12 V)
- NOMEN folding aluminum cleats (instead of standard)
- Aft fairleads
- · 3 folding blades propeller
- White or black composite steering wheels (Incompatible with First Line Pack)
- · Complete mooring/anchoring kit
- · Windlass control with chain counter in cockpit
- Outboard engine bracket (Incompatible with Tender Pack)
- Opening transom remote control
- · Shore freshwater supply
- Deck wash with fresh water / sea water
- 1 Additional opening porthole, in the aft cabins (in coaming)
- Electric engine controls + Bow thruster control, on the starboard console (only with the 7" screens)
- Large swimming ladder attached to the aft platform (instead of standard)



General Equipment list - North America

INTERIOR EQUIPMENT __

LAYOUT VERSIONS

- · 3 cabins 3 heads version
- · 4 cabins 2 heads version
- · 4 cabins 4 heads version
- · 5 cabins 3 heads version

AMBIANT

- · Alpi white oak wood interior
- Brown oak laminated floors (only with Alpi white oak woodwork)
- · Interior upholstery, according to swatches: Fabric, Leather, Ultraleather
- · Upholstery padding (Salon and Cabins): Macadamia

MULTIMEDIA

- Folding 32" LED TV in the salon
- TV LED 22" in the forward cabin
- · BOSE speaker upgrade in the salon

DOMESTIC APPLIANCES

- · Dishwasher for 6 sets (Only in lengthways galley counter version)
- Microwave oven (20 L)

ON BOARD COMFORT EQUIPMENT

- · Berth in salon
- · Spring mattress in the cabins
- Pleated shades in the salon (Hull portlights)
- Lithium batteries (to replace the AGM batteries, requires Confort trim level)
- Additional water tanks (200 L / 53 US Gal), under starboard aft berth
- Extra diesel tanks (200 L / 53 US Gal), under starboard aft berth
- 7,5 KVA 230 V / 50 Hz Generator
- Water maker (60 L/h / 16 US Gal/h)
- Air conditioning 36 000 BTU (+ Shore socket extension cord 15 m / 49'3'')
 Diesel heater "air pulse"
- 12/230 V, 2 kVA inverter
- · Quiet Flush electric toilets fresh water/Sea water
- Sea water/fresh water foot pump (Galley)